



NO.1123110130

检 测 报 告

Test Report

样品名称： 聚合物锂离子电池 903050 3000mAh 3.7V 11.1Wh 1S2P

Name of Sample: /

委托单位： 宁波鸿源电子科技有限公司

Consignor: /



上海化工院检测有限公司

Shanghai Institute of Chemical Industry Testing Co., Ltd.

上海化工院检测有限公司

检测报告

Shanghai Institute of Chemical Industry
Testing Co., Ltd. Test Report

NO. 1123110130

1/11

样品名称 Name of Sample	中文 Chinese	聚合物锂离子电池 903050 3000mAh 3.7V 11.1Wh 1S2P	
	英文 English	/	
样品编号 Sample No.	1123110130		
检测方法 Test method	联合国《试验和标准手册》 ST/SG/AC. 10/11/Rev. 7&Amend. 1 38.3 UN Manual of Tests and Criteria ST/SG/AC. 10/11/Rev. 7&Amend. 1 Section 38.3		
判定标准 Criterion	联合国《试验和标准手册》 ST/SG/AC. 10/11/Rev. 7&Amend. 1 38.3 UN Manual of Tests and Criteria ST/SG/AC. 10/11/Rev. 7&Amend. 1 Section 38.3		
样品外观 Appearance	蓝色 塑料薄膜外壳 Blue Plastic film shell		
样品接受日期 Accepted Date	2023-11-06	检测起迄日期 Test Date	2023-11-14 ~ 2023-12-12
检测项目 Test Items	高度模拟;热测试;振动;冲击;外短路;挤压;过充电;强制放电 Altitude simulation, Thermal test, Vibration, Shock, External short circuit, Crush, Overcharge, Forced discharge		
检测结论 Conclusion	经检测, 该样品符合联合国《试验和标准手册》ST/SG/AC. 10/11/Rev. 7&Amend. 1 38.3标准要求。 The sample has passed the test items of UN Manual of Tests and Criteria ST/SG/AC. 10/11/Rev. 7&Amend. 1 Section 38.3 生效日期(Date): 2023-12-13		
备注 Comment	可充电锂电池组Rechargeable Lithium Battery./		
委托单位地址 Consignor Address	/		邮政编码 Post Code /

批准
Approver:
职务
Title:

许尧

审核
Checker:

陈建峰

编制
Compiler:

傅强

电化学测试部部长(Head of Electrochemical Testing Department)



上海化工院检测有限公司

检测报告

Shanghai Institute of Chemical Industry
Testing Co., Ltd. Test Report

NO. 1123110130

2/11

序号 No.	检测项目名称 Name of Test Items	标准要求或标准条款号 Standard requirement or The Clause Number of Standard	检测结果 Test Result	本项结论 Conclusion	备注 Remark
1	高度模拟 Altitude simulation	联合国《试验和标准手册》ST/SG/AC. 10/11/Rev. 7&Amend. 1 38.3 试验T.1 UN Manual of Tests and Criteria ST/SG/AC. 10/11/Rev. 7&Amend. 1 Section 38.3 Test T.1	见附表 1 See Appendix 1	合格 Passed	/
2	热测试 Thermal test	联合国《试验和标准手册》ST/SG/AC. 10/11/Rev. 7&Amend. 1 38.3 试验T.2 UN Manual of Tests and Criteria ST/SG/AC. 10/11/Rev. 7&Amend. 1 Section 38.3 Test T.2	见附表 2 See Appendix 2	合格 Passed	/
3	振动 Vibration	联合国《试验和标准手册》ST/SG/AC. 10/11/Rev. 7&Amend. 1 38.3 试验T.3 UN Manual of Tests and Criteria ST/SG/AC. 10/11/Rev. 7&Amend. 1 Section 38.3 Test T.3	见附表 3 See Appendix 3	合格 Passed	/
4	冲击 Shock	联合国《试验和标准手册》ST/SG/AC. 10/11/Rev. 7&Amend. 1 38.3 试验T.4 UN Manual of Tests and Criteria ST/SG/AC. 10/11/Rev. 7&Amend. 1 Section 38.3 Test T.4	见附表 4 See Appendix 4	合格 Passed	/
5	外短路 External short circuit	联合国《试验和标准手册》ST/SG/AC. 10/11/Rev. 7&Amend. 1 38.3 试验T.5 UN Manual of Tests and Criteria ST/SG/AC. 10/11/Rev. 7&Amend. 1 Section 38.3 Test T.5	见附表 5 See Appendix 5	合格 Passed	/
6	挤压 Crush	联合国《试验和标准手册》ST/SG/AC. 10/11/Rev. 7&Amend. 1 38.3 试验T.6 UN Manual of Tests and Criteria ST/SG/AC. 10/11/Rev. 7&Amend. 1 Section 38.3 Test T.6	见附表 6 See Appendix 6	合格 Passed	/
7	过充电 Overcharge	联合国《试验和标准手册》ST/SG/AC. 10/11/Rev. 7&Amend. 1 38.3 试验T.7 UN Manual of Tests and Criteria ST/SG/AC. 10/11/Rev. 7&Amend. 1 Section 38.3 Test T.7	见附表 7 See Appendix 7	合格 Passed	/
8	强制放电 Forced discharge	联合国《试验和标准手册》ST/SG/AC. 10/11/Rev. 7&Amend. 1 38.3 试验T.8 UN Manual of Tests and Criteria ST/SG/AC. 10/11/Rev. 7&Amend. 1 Section 38.3 Test T.8	见附表 8 See Appendix 8	合格 Passed	/
检测环境条件 Test Environment Condition		环境温度:21℃-22℃;环境湿度:/% Ambient temperature:21℃-22℃;Ambient humidity:/%			
分包检验情况 Subcontracted Test Condition		检测项目 Test Item	/		
		分包实验室 Subcontracted Laboratory	名称 Name	/	邮编 Post Code
			地址 Address	/	电话 Tel

检测报告-附表2

NO. 1123110130

4/11

备注: L-泄漏 V-漏气 D-解体 R-破裂 F-起火 O-无泄漏、无漏气、无解体、无破裂、无起火。
Note: L-Leakage V-Venting D-Disassembly R-Rupture F-Fire O-No Leakage, No Venting,
No Disassembly, No Rupture & No Fire.

备注: L-泄漏 V-漏气 D-解体 R-破裂 F-起火 O-无泄漏、无漏气、无解体、无破裂、无起火。
Note: L-Leakage V-Venting D-Disassembly R-Rupture F-Fire O-No Leakage, No Venting,
No Disassembly, No Rupture & No Fire.

检测报告-附表3

NO. 1123110130

5/11

备注: L-泄漏 V-漏气 D-解体 R-破裂 F-起火 O-无泄漏、无漏气、无解体、无破裂、无起火。
Note: L-Leakage V-Venting D-Disassembly R-Rupture F-Fire O-No Leakage, No Venting,
No Disassembly, No Rupture & No Fire.

备注: L-泄漏 V-漏气 D-解体 R-破裂 F-起火 O-无泄漏、无漏气、无解体、无破裂、无起火。
Note: L-Leakage V-Venting D-Disassembly R-Rupture F-Fire O-No Leakage, No Venting,
No Disassembly, No Rupture & No Fire.

检测报告-附表5

Shanghai Institute of Chemical Industry
Testing Co., Ltd. Test Report—Appendix 5

NO. 1123110130

7/11

序号 No.	5	检测项目名称 Name of Test Items	外短路 External short circuit
样品编号 Sample No.	样品状态 Sample Status	样品表面最高温度 Max. External Temperature /°C	其他现象 Other Event
001	1CYC完全充电 1CYC Fully charged	57.5	O
002	1CYC完全充电 1CYC Fully charged	56.8	O
003	1CYC完全充电 1CYC Fully charged	57.1	O
004	1CYC完全充电 1CYC Fully charged	57.5	O
005	25CYC完全充电 25CYC Fully charged	56.9	O
006	25CYC完全充电 25CYC Fully charged	56.7	O
007	25CYC完全充电 25CYC Fully charged	58.0	O
008	25CYC完全充电 25CYC Fully charged	56.8	O
以下空白	This space intentionally left blank		

备注：D-解体 R-破裂 F-起火 O-无解体、无起火、无破裂。
Note: D-Disassembly R-Ruptur F-Fire O-No Disassembly,No Fire & No Rupture.

检测报告-附表6

Testing Co., Ltd. Test Report—Appendix 6

8/11

序号 No.	6	检测项目名称 Name of Test Items	挤压 Crush
样品编号 Sample No.	样品状态 Sample Status	样品表面最高温度 Max. External Temperature /℃	其他现象 Other Event
009	1CYC 50%容量 1CYC 50% Capacity	22.0	O
010	1CYC 50%容量 1CYC 50% Capacity	21.7	O
011	1CYC 50%容量 1CYC 50% Capacity	22.0	O
012	1CYC 50%容量 1CYC 50% Capacity	21.2	O
013	1CYC 50%容量 1CYC 50% Capacity	21.3	O
014	25CYC 50%容量 25CYC 50% Capacity	22.0	O
015	25CYC 50%容量 25CYC 50% Capacity	21.4	O
016	25CYC 50%容量 25CYC 50% Capacity	22.0	O
017	25CYC 50%容量 25CYC 50% Capacity	21.7	O
018	25CYC 50%容量 25CYC 50% Capacity	21.5	O
以下空白	This space intentionally left blank		

备注：D-解体 F-起火 O-无解体、无起火。
Note: D-Disassembly F-Fire O-No Disassembly & No Fire.

上海化工院检测有限公司





检测报告 - 附表8

Shanghai Institute of Chemical Industry
Testing Co., Ltd. Test Report — Appendix 8

NO. 1123110130

10/11

序号 No.	8	检测项目名称 Name of Test Items	强制放电 Forced discharge
样品编号 Sample No.	样品状态 Sample Status	其他现象 Other Event	
027	1CYC完全放电 1CYC Fully discharged	O	
028	1CYC完全放电 1CYC Fully discharged	O	
029	1CYC完全放电 1CYC Fully discharged	O	
030	1CYC完全放电 1CYC Fully discharged	O	
031	1CYC完全放电 1CYC Fully discharged	O	
032	1CYC完全放电 1CYC Fully discharged	O	
033	1CYC完全放电 1CYC Fully discharged	O	
034	1CYC完全放电 1CYC Fully discharged	O	
035	1CYC完全放电 1CYC Fully discharged	O	
036	1CYC完全放电 1CYC Fully discharged	O	
037	25CYC完全放电 25CYC Fully discharged	O	
038	25CYC完全放电 25CYC Fully discharged	O	
039	25CYC完全放电 25CYC Fully discharged	O	
040	25CYC完全放电 25CYC Fully discharged	O	
041	25CYC完全放电 25CYC Fully discharged	O	
042	25CYC完全放电 25CYC Fully discharged	O	
043	25CYC完全放电 25CYC Fully discharged	O	
044	25CYC完全放电 25CYC Fully discharged	O	
045	25CYC完全放电 25CYC Fully discharged	O	
046	25CYC完全放电 25CYC Fully discharged	O	
备注：D-解体 F-起火 O-无解体、无起火。 Note: D-Disassembly F-Fire O-No Disassembly & No Fire.			



报告结束